

SENSOR FLOAT® Control Switch

Mercury-activated, narrow-angle float switch designed to activate pump control panels and alarms.

This narrow-angle sensing device is used to accurately monitor liquid levels in sewage and non-potable water applications. The Sensor Float® control switch is not sensitive to rotation and is suitable for use with intrinsically safe circuits. Contact SJE-Rhombus regarding specific intrinsically safe applications.

Normally Open Model (high level)

The control switch turns on (closes) when the float tips slightly **above** horizontal signaling a high level, and turns off (opens) when the float drops slightly below horizontal.

Normally Closed Model (low level)

The control switch turns on (closes) when the float drops slightly **below** horizontal signaling a low level, and turns off (opens) when the float tips slightly above horizontal.



FEATURES

- Suitable for use with intrinsically safe circuits.
- Not sensitive to rotation.
- Control differential of .5 inches (1 cm) above or below horizontal.
- UL Listed for use in non-potable water and sewage.
- CSA Certified.
- Three-year limited warranty.



SPECIFICATIONS

CABLE: flexible 18 gauge, 2 conductor (UL, CSA) SJOW, water-resistant (CPE) jacket

FLOAT: 3.38 inch diameter x 4.55 inch long (8.58 cm x 11.56 cm), high-impact, corrosion resistant, PVC housing for use in sewage and non-potable water up to 140°F (60°C)

MAXIMUM WATER DEPTH: 30 feet (9 meters), 13 psi

MERCURY TILT SWITCH: single pole, single throw, mercury-to-mercury contacts, hermetically sealed in a steel capsule and epoxy sealed in the float housing

ELECTRICAL: 5 amp, 120/230 VAC, 50/60 Hz

OPTIONS

This switch is available:

- for normally open (high level) applications or normally closed (low level) applications.
- in standard cable lengths of 10, 15, 20, or 30 feet and 3, 5, 6, or 10 meters.
- with three mounting options that allow for flexibility in installation:
 - Mounting Clamp:** for applications where the switch can be attached to a discharge pipe or similar mounting device.

Internally Weighted: for applications where the switch can be suspended from above.

Externally Weighted: for applications where the switch can be suspended from above.

**SJE
Rhombus®**

PO Box 1708, Detroit Lakes, MN 56502

1-888-DIAL-SJE • 1-218-847-1317

1-218-847-4617 Fax

email: sje@sjerhombus.com

www.sjerhombus.com

SEE BACKSIDE FOR ORDERING INFORMATION.
SEE PRICE BOOK FOR LIST PRICE.

SENSOR FLOAT® Control Switch

Mercury-activated, narrow-angle float switch designed to activate pump control panels and alarms.

ORDERING INFORMATION

Normally Open		Normally Closed		Shipping Weight
Part #	Description	Part #	Description	
1002108	10PCNO	1002111	10PCNC	1.29 lbs.
1002072	10SWINO	1002075	10SWINC	1.85 lbs.
1002143	10SWENO	1002146	10SWENC	3.26 lbs.
1002117	15PCNO	1002120	15PCNC	1.64 lbs.
1002080	15SWINO	1002083	15SWINC	2.22 lbs.
1002152	15SWENO	1002155	15SWENC	3.50 lbs.
1002125	20PCNO	1002128	20PCNC	1.99 lbs.
1002089	20SWINO	1002092	20SWINC	2.59 lbs.
1002161	20SWENO	1002164	20SWENC	3.87 lbs.
1002134	30PCNO	1002137	30PCNC	2.13 lbs.
1002098	30SWINO	1002101	30SWINC	3.28 lbs.
1002170	30SWENO	1002173	30SWENC	4.48 lbs.

PC = Pipe Clamp WI = Weighted Internally WE = Weighted Externally

NO = Normally Open NC = Normally Closed

NOTE: Descriptions are grouped by cable length measured in feet (10, 15, 20, 30).

SEE PRICE BOOK FOR LIST PRICE.

OPTIONS

PACKAGING

Bagged - standard

Boxed - optional

Bulk - optional

No Mounting -

deduct optional

ADDITIONAL CABLE

Additional cable length over 30 feet is available.



SPECIFICATIONS

CABLE: flexible 18 gauge, 2 conductor (UL, CSA) SJOW, water-resistant (CPE) jacket

FLOAT: 3.38 inch diameter x 4.55 inch long (8.58 cm x 11.56 cm), high impact, corrosion resistant, PVC housing for use in sewage and non-potable water up to 140°F (60°C)

MAXIMUM WATER DEPTH: 30 feet (9 meters), 13 psi

MERCURY SWITCH: single pole, single throw, mercury-to-mercury contacts, hermetically sealed in a steel capsule and epoxy sealed in the float housing

ELECTRICAL: 5 amp 120-/230 VAC, 50/60 Hz

NOTE: Suitable for use with intrinsically safe circuits

Contact SJE-Rhombus regarding specific intrinsically safe applications.

OTHER INFORMATION

NORMALLY OPEN (HIGH LEVEL) OPERATION

The control switch closes (turns on) when the float tips slightly **above** horizontal signaling a high level, and opens (turns off) when the float drops slightly **below** normal.

NORMALLY CLOSED (LOW LEVEL) OPERATION

The control switch closes (turns on) when the float drops slightly **below** horizontal signaling a low level, and opens (turns off) when the float tips slightly **above** horizontal.

SJE
Rhombus

www.sjerhombus.com
sje@sjerhombus.com

Call or fax your order!

1-888-DIAL-SJE (1-888-342-5753) ■ Fax 218-847-4617