

Pipe sealing bags and bypass bags FS



- For pipes with diameter up to 140 cm (55 inch)
- Good resistance to chemicals
- Withstands counterpressure up to 5 m WC (7.25 psi)
- Very high resistance to heat



www.vetter.de/vetter_emergency/en/Rescue+Products/Sealing+Pipelines+and+Gullies/Pipe+sealing+bags+and+bypass+bags+FS.html

Safely seal or divert pipes.

Protect sewage systems and ground water from serious contamination. Vetter pipe sealing bags FS help your team stop hazardous substances quickly. With Vetter bypass bags, you can dam up hazardous liquids and gases and divert them controlled using a fire hose. Vetter's pipe sealing bags and bypass bags FS were specifically designed and developed for fire services. The bags individually adjust to different line diameters and are especially resistant to chemicals as well as heat.

Emergency Pneumatics

Technical data

- Working pressure: 1.5 bar (21.75 psi)
- Test pressure: 1.95 bar (28.5 psi)
- Test counterpressure: 5 m water column (7.25 psi)

Product	Art. no.	Bypass-size " / "	Pipe diameter cm / inch	Diameter cm / inch	Cylinder-length cm / inch	Total-length cm / inch	Air requirement, at working pressure litres / cu.ft.	Weight, approx. kg / lbs
RDK 7/15 FS	1482000700		7-15 3-6	6,8 2,7	30 12	34,5 13,6	9,5 0,3	0,5 1,1
RDK 10/20 FS	1482000800		10-20 4-8	9,0 3,5	51 20	55,5 21,9	28,8 1,0	0,9 2,0
RDK 20/40 FS	1482000900		20-40 8-16	19,5 7,7	51 20,1	57 22,4	112,0 3,9	3,1 6,8
RDK 30/60 FS	1482001000		30-60 12-24	29,5 11,6	73,5 28,9	78 30,7	362,5 12,8	7,3 16,1
RDK 50/100 FS	1482001100		50-100 20-40	45,0 17,7	111 43,7	117 46,1	1525 53,8	16,5 36,4
RDK 80/140 FS	1482001200		80-140 32-55	78,5 30,9	181 71,3	185,5 73,0	3125 110,3	48 105,8
BK 7/15 FS	1483002200	1" 1	7-15 3-6	6,8 2,7	30 12	36 14,2	6,4 0,2	3,4 7,5
BK 10/20 FS	1483001400	2 1/2" 2 1/2	10-20 4-8	9,7 3,8	48,5 19,1	55,5 21,9	22,5 0,8	3,4 7,5
BK 20/50 FS	1483001500	4" 4	20-50 8-20	19,5 7,7	55 21,7	67 26,4	157,5 5,6	9,4 20,7
BK 50/120 FS	1483001600	4" 4	50-120 20-47	45 17,7	92 36,2	94 37	1420 50,1	52,2 115,1
BK 80/140 FS	1483001000	4" 4	80-140 32-55	78,5 30,9	181 71,3	193 76	3075 108,6	69 152,2

Accessories

- Inflation hoses 1.5 bar (21.75 psi)
- Controllers 1.5 bar (21.75 psi)
- Foot pump 1.5 bar (21.75)
- Inflation with cylinder
- Inflation with alternative air source



In operation...

- Holding back and diverting liquids/ fumes
- Sealing the openings of tank trucks and wagons
- Creating a pump sump
- In pipelines



Good reasons...

- Various sizes available to seal pipe diameters 7 - 140 cm (2.7 - 55 inch)
- Short- term resistance to temperatures up to 115 °C (239 °F) and long- term resistance to temperatures up to 90 °C (194 °F)



Guaranteed quality:

- Individually tested (with dated inspection seal)
- High- quality rubber with high resistance to chemicals

Please contact us directly should you have any further questions concerning this product.

Sales Germany
Phone.: +49 (0) 22 52 / 30 08-50
Fax: +49 (0) 22 52 / 30 08-70
E- Mail: vetter.info@idexcorp.com

Sales international
Phone.: +49 (0) 22 52 / 30 08-60
Fax: +49 (0) 22 52 / 30 08-71
E- Mail: vetter.info@idexcorp.com

Or find the nearest dealer under:
[www.vetter.de/ support/ haendler](http://www.vetter.de/support/haendler)
